

## SPECIFICATIONS

### Xthermostat™ TS 400



The Xthermostat™ TS400 is a din-rail thermostat suitable to be mounted in the switchboard. It is compatible with all home-automation systems such as C-Bus and recommended for systems connected to Off-Peak power supply.

## DESCRIPTION

- Should be installed inside a protected enclosure.
- Contactors are required where the total load in a zone exceeds 75% of the carrying capacity of the thermostat (max 2,700W, 12A for a thermostat marked 16A).

## TECHNICAL FEATURES

<b>Sensing type</b>	Floor (external sensor)
<b>Mounting</b>	DIN Rail mounted
<b>Measuring accuracy</b>	+/- 0.5°C
<b>Operating temperature</b>	0°C - 50°C
<b>Setting temperature range</b>	5°C - 45°C TBC
<b>Regulation characteristics</b>	Static differential
<b>Electrical protection</b>	Class II - IP20
<b>Main switch</b>	No
<b>Power supply</b>	230Vac +/- 10% 50Hz
<b>Output</b>	Relay 16A 250Vac resistive load (AC1)
<b>Type of external sensor</b>	NTC - 15 kOhms at 25°C

p: 1800 636 091 | e: [info@devexsystems.com.au](mailto:info@devexsystems.com.au) | w: [www.devexsystems.com.au](http://www.devexsystems.com.au)